



Double Wheel Rotary Ditcher

OVERVIEW:

This fully imported Italian DONDI double-wheel rotary ditchers offers the highest level of technology and performance for digging and maintaining drainage and irrigation ditches.

They can be used on any wheeled tractor with creep speeds of 0.4 / 0.6 for digging new ditches, while a higher advancement speed of up to 1.2 Km/h can be used for simple maintenance work. The standard digging angle is 32°, and digging angles of 18°, 20°, 23°, 42° are available on request in order to adapt to different types of soil and various needs.

In order to use the ditchers, the tractor must be ballasted in the front. The ditch is dug in one or more passages, depending on the type of soil, tractor power and advancement speed.

The excavated soil is distributed evenly on both sides. On request, supplementary rubber covers are also available.

Work depth is regulated via the hydraulic hoist of the tractor in a controlled position.

OPTIONAL FEATURES:

Transport wheel

Three-point hydraulic hitch

Hydraulic regulation of the side covers

Cardan shaft with safety clutch.



MODEL	HP POWER	km/h TRACTOR SPEED	rpm PTO	MAXIMUM WORK DIMENSIONS	Kg WEIGHT
DBR.65 R/32	70-75	0,4 / 0,6	540	32° 137 30 85	830
DBR.65 R/32	70-75	0,4 / 0,6	1000	32° 137 30 85	830
DBR.75/32	75-85	0,4 / 0,6	540	32° 154 30 100	970
DBR.75/32	75-85	0,4 / 0,6	1000	32° 154 30 100	970
DBR.90/32	95-110	0,4 / 0,6	1000	32° 176 34 115	1240
DBR.95/32	110-140	0,4 / 0,6	1000	32° 190 34 130	1400

Roadking
Manufacturing (Pty)Ltd

ENQUIRIES & ORDERS:

Office+27 (0) 86 033 3110

Cell +27(0) 82 4687094

info@roadkingsa.co.za

www.roadkingsa.co.za