



DRENAG VERTICAL TRENCH CUTTING DEVICE



DONDI DRENAG is effective on any type of rock-free soil to open drainage ditches and lay drainage and irrigation pipes, electrical and telephone cables, and pipes for water mains with a maximum diameter of 150 mm.

DONDI DRENAG is used on the three-point hitch of any type of tractor with wheels with creep speeds of 0.35 / 0.65 Km/h and is driven by a power takeoff at 540 and 1000 rpm. The work depth is adjusted via hydraulic hoist of the tractor and a hydraulic jack on the DRENAG performs the startup operation until the desired depth is achieved.

The different cutting widths are obtained simply by inverting the position of the blades on the 8- and 14- cm rotor disk and with a kit of pads to

The excavated soil can be removed laterally or can be left near the ditch to fill it after the pipes have been laid.

On request, the DRENAG 75/100 and 100/120 can be outfitted with a complete kit for de reeling pipes and/or cables while the ditching is under way.

DONDI DRENAG is delivered complete with a Cardan shaft, safety clutch and third-point hydraulic hitch in the 75/100 and 100/120 models. When working with hard and rocky soils, the machine can also be equipped with tools with tungsten bits.



OPTIONAL FEATURES:

Complete kit for pipe-laying device

Complete kit for 20 cm cutting section

Third-point hydraulic hitch for DRENAG 50

modello model

DRENAG 50-540
DRENAG 60-540
DRENAG 75/100-540
DRENAG 75/100-1000
DRENAG 100/120-1000

HP	kW	km/h	rpm	cm	Kg
----	----	------	-----	----	----

60-68	45-51	0,35/0,65	540	50	8-14	460
70-90	52-67	0,35/0,65	540	60	8-14	510
90-110	67-82	0,35/0,65	540	75	8-14-20	960
90-110	67-82	0,35/0,65	1000	75	8-14-20	960
140-170	104-127	0,35/0,65	1000	100	8-14-20	1800

codice code

D225001
D225005
D225002
D225003
D225004

Roadking
Manufacturing (Pty)Ltd

ENQUIRIES & ORDERS:

+27 (0) 86 033 3110

+27 (0) 82 468 7094

info@roadkingsa.co.za